

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
28 February 2002 (28.02.2002)

PCT

(10) International Publication Number
WO 02/16205 A1

(51) International Patent Classification⁷: **B65B 9/04**,
11/50, B65D 65/46

(21) International Application Number: PCT/GB01/03790

(22) International Filing Date: 23 August 2001 (23.08.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0021113.6 25 August 2000 (25.08.2000) GB

(71) Applicant (for all designated States except US):
RECKITT BENCKISER (UK) LIMITED [GB/GB];
103-105 Bath Road, Slough, Berkshire SL1 3UH (GB).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **DUFFIELD, Paul,**
John [GB/GB]; 128 Canada Drive, Cherry Burton, Bever-
ley, East Yorkshire HU17 7RH (GB).

(74) Agents: **DICKSON, Elizabeth, Anne** et al.; Reckitt
Benckiser plc, Group Patents Dept., Dansom Lane, Hull
HU8 7DS (GB).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, PH, PL, PT, RO, RU, SD, SE, SG, SI,
SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU,
ZA, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,
IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF,
CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD,
TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.



WO 02/16205 A1

(54) Title: WATER-SOLUBLE THERMOFORMED CONTAINERS COMPRISING AQUEOUS COMPOSITIONS

(57) Abstract: A process for preparing a water-soluble container which comprises: a) thermoforming a first poly(vinyl alcohol) film having a water content of less than 5 wt% to produce a pocket; b) filling the pocket with a composition; c) placing a second film on top of the filled pocket; and d) sealing the first film and second film together.

WATER-SOLUBLE THERMOFORMED CONTAINERS COMPRISING AQUEOUS
COMPOSITIONS

The present invention relates to a process for preparing
5 water-soluble containers from a poly(vinyl alcohol) (PVOH)
film.

It is known to package chemical compositions which may be of
a hazardous or irritant nature in water-soluble or water-
10 dispersible materials such as films. The package can simply
be added to water in order to dissolve or disperse the
contents of the package into the water.

It is known to form water-soluble containers by
15 thermoforming a water-soluble material. For example,
WO 92/17382 discloses a package containing an
agrochemical such as a pesticide comprising a first sheet of
non-planar water-soluble or water-dispersible material and a
second sheet of water-soluble or water-dispersible material
20 superposed on the first sheet and sealed to it by a
continuous closed water-soluble or water-dispersible seal
along a continuous region of the superposed sheets. It is
stated to be advantageous to ensure that the package
produced is evacuated of air or the contents are under
25 reduced pressure to provide increased resistance to shock.

In fields such as detergents for domestic use, an attractive
appearance for an article is extremely desirable. However,
in the prior art such as that described above, the packages
30 do not have an attractive appearance. For example, the
packages disclosed in WO 92/17382 are likely to have a non-

uniform appearance because they are packaged under reduced pressure.

We have discovered that this type of product is not deemed
5 to be attractive by an average consumer.

The present invention seeks to provide a water-soluble container containing a composition, which container has a more attractive appearance. In particular the container
10 should be relatively self-supporting and look full. Ideally the container should have an attractive, rounded three-dimensional appearance.

Commercially available PVOH film is generally prepared by a
15 blown or casting process. In both types of process the film picks up a certain degree of moisture because PVOH is hydroscopic. In general, commercially available film contains around 6 to 14 wt% water, especially about 8 wt% water. When thermoforming containers by the method
20 disclosed in WO 92/17382, the initially thermoformed PVOH pocket shrinks before the pocket can be filled. Thus, even in the short time of around 5 to 20 seconds before the pocket is filled on a commercial production line, the volume of the pocket can diminish by up to 50%.

25

We have surprisingly discovered that if the PVOH film is substantially anhydrous, that is containing less than 5 wt% water, there is little or no shrinkage. It is therefore possible to fill the pocket to or near the brim without a
30 substantial risk of overflow as the pocket continues to contract. The second sheet of water-soluble material can

then be placed on the first sheet and sealed to it. Thus the containers can safely be filled to a greater extent than those described in WO 92/17382, which in itself can impart a significantly more attractive appearance to the containers.

5

The individual containers thus produced will, after time, start to absorb moisture either from the air or from the composition held within the film if it is an aqueous liquid composition containing free water. Immediately after the
10 containers are prepared, they may be limp if not completely filled. However, after this storage they will develop a more attractive three-dimensional appearance and also appear to look even fuller. They can also be said to have a "puffed-up" appearance. Although not bound by this theory, it is
15 believed that the water in the aqueous composition held within the container or from the atmosphere shrinks the PVOH film, which was stretched during the thermoforming process, around the composition to provide the attractive appearance. In other words the PVOH film attempts to recover its
20 original shape when contacted with the aqueous composition.

Thus the present invention provides a process for preparing a water-soluble container which comprises:

- a) thermoforming a first PVOH film having a water content
25 of less than 5 wt% to produce a pocket;
- b) filling the pocket with a composition;
- c) placing a second film, preferably a PVOH film, on top of the filled pocket; and
- d) sealing the first film and second film together.

30

The present invention also provides the use of a thermoformed PVOH film containing less than 5 wt% water to package a composition.

- 5 The present invention additionally provides the use of a PVOH film containing less than 5 wt% water and comprising 15 to 20 wt% plasticiser, based on the total weight of the film, to package a composition.
- 10 If more than one PVOH film is used, the films may be identical or different. The PVOH film may be partially or fully alcoholised or hydrolysed, for example, it may be from 40 to 100%, preferably 70 to 92%, most preferably about 88% or about 92%, alcoholised or hydrolysed, polyvinyl acetate
- 15 film. The degree of hydrolysis is known to influence the temperature at which the PVOH starts to dissolve in water. 88% hydrolysis corresponds to a film soluble in cold (i.e. room temperature) water, whereas 92% hydrolysis corresponds to a film soluble in warm water. An example of a preferred
- 20 PVOH is ethoxylated PVOH. The film may be cast, blown or extruded. It may also be unorientated, mono-axially oriented or bi-axially oriented.

- It is possible for suitable additives such as plasticisers,
- 25 lubricants and colouring agents to be added to the film. Components which modify the properties of the polymer may also be added. Plasticisers are generally used in an amount of up to 35 wt%, for example from 5 to 35 wt%, preferably from 7 to 20 wt%, more preferably from 10 to 15 wt%.
- 30 Lubricants are generally used in an amount of 0.5 to 5 wt%. The polymer is therefore generally used in an amount of from

60 to 94.5 wt%, based on the total amount of the composition used to form the film. Suitable plasticisers are, for example, pentaerythritols such as depentaerythritol, sorbitol, mannitol, glycerine and glycols such as glycerol, ethylene glycol and polyethylene glycol. Solids such as talc, stearic acid, magnesium stearate, silicon dioxide, zinc stearate or colloidal silica may also be used.

It is also possible to include one or more particulate solids in the films in order to accelerate the rate of dissolution of the container. This solid may also be present in the contents of the container. Dissolution of the solid in water is sufficient to cause an acceleration in the break-up of the container, particularly if a gas is generated, when the physical agitation caused may, for example, result in the virtually immediate release of the contents from the container. Examples of such solids are alkali or alkaline earth metal, such as sodium, potassium, magnesium or calcium, bicarbonate or carbonate, in conjunction with an acid. Suitable acids are, for example, acidic substances having carboxylic or sulfonic acid groups or salts thereof. Examples are cinnamic, tartaric, mandelic, fumaric, maleic, malic, palmoic, citric and naphthalene disulfonic acids.

25

The film is generally cold water (20°C) soluble, but may be insoluble in cold water at 20°C and only become soluble in warm water or hot water having a temperature of, for example, 30°C, 40°C, 50°C or even 60°C. This parameter is determined in the case of PVOH by its degree of hydrolysis.

30

It is particularly important to avoid pinholes in the film through which leakage of the contained composition may occur.. It may therefore be appropriate to use a laminate of two or more layers of a different or the same film, as
5 pinholes are unlikely to coincide in two layers of material.

Since all commercially available PVOH film contains around 6 to 14 wt% water, it is necessary to take special steps to obtain a film having a water content of less than 5 wt%
10 (herein sometimes referred to as an anhydrous film). A blown PVOH film initially contains a very low proportion of water and can be considered to be anhydrous. However, it rapidly absorbs water from the atmosphere until it contains around 8 wt% water or even more. It is therefore possible
15 to obtain an anhydrous PVOH film by immediately wrapping a blown PVOH film in packaging which prevents moisture absorption, such as a polyethylene film. Another possibility is to carry out the thermoforming process on a PVOH blown film immediately after it has been prepared. A
20 further possibility is to dry a blown or cast PVOH film, by storing it open under reduced humidity conditions, although this may not be commercially economic.

Desirably the PVOH film contains less than 4 wt% water,
25 preferably less than 3 wt%, 2 wt% or 1 wt% water. In general it is difficult to obtain a totally anhydrous PVOH film, but desirably the film contains more than 0.1wt% water, for example more than 0.5wt% or more than 1 wt% water, to ensure the film is not too brittle. Most
30 preferably the film contains 0.5 to 1 wt% of water. The amount of water required to ensure that the film is not too

brittle depends to a certain extent on the amount of plasticiser in the film.

The method of forming the container is similar to the method described in WO 92/17382 except for using an anhydrous PVOH film. A first PVOH film is initially thermoformed to produce a non-planar sheet containing a pocket, such as a recess, which is able to retain the composition. The pocket is generally bounded by a flange, which is preferably substantially planar. The pocket may have internal barrier layers as described in, for example, WO 93/08095.

The pocket is then filled with the composition. Unlike the process described in WO 92/17382, the pocket does not have to be immediately filled. Since the anhydrous film has a degree of shape and size stability it does not immediately shrink. Once it has been filled with the composition, a second film, preferably a PVOH film, is placed on the flange and across the pocket. The second PVOH film is desirably anhydrous, but need not be. For example it may be a normal PVOH film containing at least 6 wt%, especially around 6 to 14 or 18 wt%, more especially about 8 wt% water. The second PVOH film may or may not be thermoformed. If the first film contains more than one pocket, the second film may be placed across all of the pockets for convenience.

The pocket is desirably completely filled so that the filled containers look full. However, it is possible to leave an airspace of from 2 to 20%, especially from 5 to 10%, of the volume of the container immediately after it is formed. Partial filling may reduce the risk of rupture of the

container if it is subjected to shock and may reduce the risk of leakage if the container is subjected to high temperatures.

- 5 The films are then sealed together, for example by heat sealing across the flange. A suitable heat sealing temperature is, for example, 120 to 195°C, for example 140 to 150°C. A suitable sealing pressure is, for example, from 250 to 800 kPa. Examples of sealing pressures are 276 to 552
- 10 kPa (40 to 80 p.s.i.), especially 345 to 483 kPa (50 to 70 p.s.i.) or 400 to 800 kPa (4 to 8 bar), especially 500 to 700 kPa (5 to 7 bar) depending on the heat sealing machine used. Suitable sealing dwell times are at least 0.4 seconds, for example 0.4 to 2.5 seconds. Other methods of
- 15 sealing the films together may be used, for example infra-red, radio frequency, ultrasonic, laser, solvent, vibration, electromagnetic, hot gas, hot plate, insert bonding, fraction sealing or spin welding. An adhesive such as water or an aqueous solution of PVOH may also be used. The
- 20 adhesive can be applied to the films by spraying, transfer coating, roller coating or otherwise coating, or the films can be passed through a mist of the adhesive. The seal desirably is also water-soluble.
- 25 The first anhydrous film will generally have a thickness before thermoforming of 20 to 500 μm , especially 70 to 400 μm , for example 70 to 300 μm , most preferably 70 to 160 μm , especially 90 or 110 to 150 μm . The thickness of the second film may be less than that of the first film as the second
- 30 film will not generally be thermoformed, so localised

thinning of the sheet will not occur. The thickness of the second film will generally be from 20 to 150 or 160 μm , preferably from 40 or 50 to 90 or 100 μm , more preferably from 50 to 80 μm . However a film having a thickness of 70
5 to 150 μm may also be used.

The films may be chosen, if desired, such that they have the same thickness before the first film is thermoformed, or have the same thickness after the first sheet has been
10 thermoformed in order to provide a composition which is encapsulated by a substantially constant thickness of film.

The nature of the composition is not limited. It may, for example, be a solid or a liquid. If it is in the form of a
15 solid it may, for example, be in the form of a powder, granules, an extruded tablet, a compressed tablet or a solidified gel. If it is in the form of a liquid it may be optionally thickened or gelled with a thickener or a gelling agent. One or more than one phase may be present. For
20 example the container may be filled with a liquid composition and a separate solid composition, for example in the form of a ball, pill or speckles. Alternatively two or more solid phases may be present, or two or more immiscible liquid phases.

25

Thus the composition need not be uniform. For example, during the manufacture the container could first be filled with a settable composition, for example a gel, and then with a different composition such as a liquid, especially an
30 aqueous, composition. The first composition could dissolve slowly, for example in a washing process, so as to deliver

its charge over a long period. This might be useful, for example, to provide an immediate, delayed or sustained delivery of a component such as a softening agent.

- 5 If the water-soluble container is soluble in cold water at room temperature (20°C) or slightly above, it is important to ensure that the composition itself does not dissolve the container. In general solid compositions will not attack the container, and neither will liquid organic compositions
10 which contain less than around 5 wt% of water, as described, for example, in WO 92/17382. If the composition is in the form of a liquid containing more than about 5 wt% water, action must be taken to ensure that the composition does not attack the walls of the container. Steps may be taken to
15 treat the inside surface of the film, for example by coating it with an agent such as PVdC (poly(vinylidene dichloride)) or PTFE (polytetrafluoroethylene). A semi-permeable or partial water barrier such as polyethylene or polypropylene or a hydrogel such as a polyacrylate may also be provided as
20 a coating. The coating will simply fall apart or dissolve or disperse into microscopic particles when the container is dissolved in water. Steps may also be taken to adapt the composition to ensure that it does not dissolve the film. For example, it has been found that ensuring the composition
25 has a high ionic strength or contains an agent which minimises water loss through the walls of the container will prevent the composition from dissolving a PVOH film from the inside. This is described in more detail in EP-A-518,689 and WO 97/27743.

The total amount of water in the composition may be more than 5 wt%, for example more than 10, 15, 20, 25 or 30 wt%. The total water content may be less than 80 wt% for example less than 70, 60, 50 or 40 wt%. It may, for example,
5 contain from 30 to 65 wt% total water.

If more than one container is formed at the same time, the packaged compositions may then be separated from each other. Alternatively, they may be left conjoined and, for example,
10 perforations provided between the individual containers so that they can be easily separated at a later stage, for example by a consumer.

If the containers are separated, the flanges may be left in
15 place. However, desirably the flanges are partially removed in order to provide an even more attractive, three-dimensional appearance. Generally the flange remaining should be as small as possible for aesthetic purposes while bearing in mind that some flange is required to ensure the
20 two films remain adhered to each other. A flange of 1 mm to 10 mm is desirable, preferably 2 mm to 7 mm, more preferably 4 mm to 6mm, most preferably about 5 mm.

The containers may then be left to absorb water from the
25 atmosphere, or may be immediately packaged into boxes for retail sale. The containers may themselves be packaged in outer containers if desired, for example non-water soluble containers which are removed before the water soluble containers are used.

The containers of the present invention generally contain from 5 to 100 g of composition, such as an aqueous composition, especially from 15 to 40 g, depending on their intended use. For example, a dishwashing composition may
5 weigh from 15 to 20 g, a water-softening composition may weigh from 25 to 35 g, and a laundry composition may weigh from 10 to 40 g, especially 20 to 30g or 30 to 40g.

The containers may have any shape. For example they can
10 take the form of an envelope, sachet, sphere, cylinder, cube or cuboid, i.e. a rectangular parallelepiped whose faces are not all equal. In general, because the containers are not rigid and are inflated, the sides are not planar, but rather are convex. If the container is formed from a thermoformed
15 film and a planar film, the seam between the two films will appear nearer one face of the container rather than the other. Apart from the deformation of the container due to shrinkage of the PVOH film after the container is manufactured, deformation may also occur at the stage of
20 manufacture if desired. For example, if the pocket is filled with a solid or gelled composition (for example in the form of a tablet) having a height greater than that of the pocket, the second film will be deformed when placed on top of the pocket.

25

In general the maximum dimension of the filled part of the container (excluding any flanges) is 5 cm. For example, a rounded cuboid container may have a length of 1 to 5 cm, especially 3.5 to 4.5 cm, a width of 1.5 to 3.5 cm,
30 especially 2 to 3 cm, and a height of 1 to 2.5 cm, especially 1 to 2 cm, for example 1.25 to 1.75 cm.

The composition filling the containers is not particularly limited. It can be any composition which is to be added to an aqueous system or used in an aqueous environment.

- 5 Desirably the composition is a fabric care, surface care or dishwashing composition. For example, the composition may comprise a dishwashing, water-softening, laundry or detergent composition or a rinse aid. In this case it is especially suitable for use in a domestic washing machine
10 such as a laundry washing machine or dishwashing machine. The container may also comprise a disinfectant, antibacterial or antiseptic composition intended to be diluted with water before use, or a concentrated refill composition, for example for a trigger-type spray used in
15 domestic situations. Such a composition can simply be added to water already held in the spray container.


- Examples of surface care compositions are those used to clean, treat or polish a surface. Suitable surfaces are,
20 for example, household surfaces such as worktops, as well as surfaces of sanitary ware, such as sinks, basins and lavatories.

- The ingredients of the composition depend on the use of the
25 composition. Thus, for example, the compositions may contain surface active agents such as anionic, nonionic, cationic, amphoteric or zwitterionic surface active agents or mixtures thereof.

- 30 Examples of anionic surfactants are straight-chained or branched alkyl sulfates and alkyl polyalkoxylated

sulfates, also known as alkyl ether sulfates. Such surfactants may be produced by the sulfation of higher C₈-C₂₀ fatty alcohols.

- 5 Examples of primary alkyl sulfate surfactants are those of formula:




wherein R is a linear C₈-C₂₀ hydrocarbyl group and M is a water-solubilising cation. Preferably R is C₁₀-C₁₆ alkyl, for
10 example C₁₂-C₁₄, and M is alkali metal such as lithium, sodium or potassium.

Examples of secondary alkyl sulfate surfactants are those which have the sulfate moiety on a "backbone" of the
15 molecule, for example those of formula:



wherein m and n are independently 2 or more, the sum of m+n typically being 6 to 20, for example 9 to 15, and M is a water-solubilising cation such as lithium, sodium or
20 potassium.


Especially preferred secondary alkyl sulfates are the (2,3) alkyl sulfate surfactants of formulae:



for the 2-sulfate and 3-sulfate, respectively. In these
30 formulae x is at least 4, for example 6 to 20, preferably 10

to 16. M is cation, such as an alkali metal, for example lithium, sodium or potassium.

Examples of alkoxyated alkyl sulfates are ethoxylated alkyl
5 sulfates of the formula:




wherein R is a C_8 - C_{20} alkyl group, preferably C_{10} - C_{18} such as a
10 C_{12} - C_{16} , n is at least 1, for example from 1 to 20, preferably
1 to 15, especially 1 to 6, and M is a salt-forming cation
such as lithium, sodium, potassium, ammonium, alkylammonium
or alkanolammonium. These compounds can provide especially
desirable fabric cleaning performance benefits when used in
15 combination with alkyl sulfates.

The alkyl sulfates and alkyl ether sulfates will generally
be used in the form of mixtures comprising varying alkyl
chain lengths and, if present, varying degrees of
20 alkoxylation.

Other anionic surfactants which may be employed are salts of
fatty acids, for example C_8 - C_{18} fatty acids, especially the
sodium, potassium or alkanolammonium salts, and alkyl, for
25 example C_8 - C_{18} , benzene sulfonates.

Examples of nonionic surfactants are fatty acid alkoxyates,
such as fatty acid ethoxyates, especially those of formula:



wherein R is a straight or branched C₈-C₁₆ alkyl group, preferably a C₉-C₁₅, for example C₁₀-C₁₄ or C₁₂-C₁₄, alkyl group and n is at least 1, for example from 1 to 16, preferably 2 to 12, more preferably 3 to 10.

5

The alkoxyated fatty alcohol nonionic surfactant will frequently have a hydrophilic-lipophilic balance (HLB) which ranges from 3 to 17, more preferably from 6 to 15, most preferably from 10 to 15.

10

Examples of fatty alcohol ethoxylates are those made from alcohols of 12 to 15 carbon atoms and which contain about 7 moles of ethylene oxide. Such materials are commercially marketed under the trademarks Neodol 25-7 and Neodol 23-6.5 by Shell Chemical Company. Other useful Neodols include Neodol 1-5, an ethoxylated fatty alcohol averaging 11 carbon atoms in its alkyl chain with about 5 moles of ethylene oxide; Neodol 23-9, an ethoxylated primary C₁₂-C₁₃ alcohol having about 9 moles of ethylene oxide; and Neodol 91-10, an ethoxylated C₉-C₁₁ primary alcohol having about 10 moles of ethylene oxide.

Alcohol ethoxylates of this type have also been marketed by Shell Chemical Company under the Dobanol trademark. Dobanol 91-5 is an ethoxylated C₉-C₁₁ fatty alcohol with an average of 5 moles ethylene oxide and Dobanol 25-7 is an ethoxylated C₁₂-C₁₅ fatty alcohol with an average of 7 moles of ethylene oxide per mole of fatty alcohol.

Other examples of suitable ethoxylated alcohol nonionic surfactants include Tergitol 15-S-7 and Tergitol 15-S-9,

both of which are linear secondary alcohol ethoxylates available from Union Carbide Corporation. Tergitol 15-S-7 is a mixed ethoxylated product of a C_{11} - C_{15} linear secondary alkanol with 7 moles of ethylene oxide and Tergitol 15-S-9
5 is the same but with 9 moles of ethylene oxide.

Other suitable alcohol ethoxylated nonionic surfactants are Neodol 45-11, which is a similar ethylene oxide condensation products of a fatty alcohol having 14-15 carbon atoms and
10 the number of ethylene oxide groups per mole being about 11. Such products are also available from Shell Chemical Company.

Further nonionic surfactants are, for example, C_{10} - C_{18} alkyl
15 polyglycosides, such as C_{12} - C_{16} alkyl polyglycosides, especially the polyglucosides. These are especially useful when high foaming compositions are desired. Further surfactants are polyhydroxy fatty acid amides, such as C_{10} - C_{18} N-(3-methoxypropyl) glycamides and ethylene oxide-propylene
20 oxide block polymers of the Pluronic type.

Examples of cationic surfactants are those of the quaternary ammonium type.

25 Examples of amphoteric surfactants are C_{10} - C_{18} amine oxides and the C_{12} - C_{18} betaines and sulfobetaines.

The total content of surfactants in a laundry or detergent composition is desirably 60 to 95 wt%, especially 70 to 90
30 wt%. Desirably, especially in a laundry composition, an anionic surfactant is present in an amount of 50 to 75 wt%,

a nonionic surfactant is present in an amount of 5 to 20 wt%, a cationic surfactant is present in an amount of from 0 to 10 wt% and/or an amphoteric surfactant is present in an amount of from 0 to 10 wt%. Desirably in a dishwashing
5 composition, the anionic surfactant is present in an amount of from 0.1 to 50%, a non-ionic surfactant is present in an amount of 0.5 to 20 wt% and/or a cationic surfactant is present in an amount of from 1 to 15 wt%. These amounts are based on the total solids content of the composition, i.e.
10 excluding any water which may be present.

Dishwashing compositions usually comprises a detergency builder. Suitable builders are alkali metal or ammonium phosphates, polyphosphates, phosphonates, polyphosphonates,
15 carbonates, bicarbonates, borates, polyhydroxysulfonates, polyacetates, carboxylates and polycarboxylates such as citrates. The builder is desirably present in an amount of up to 90wt% preferably 15 to 90wt%. More preferably 15 to 75wt%, relative to the total content of the composition.
20 Further details of suitable components are given in, for example, EP-A-694,059, EP-A-518,720 and WO 99/06522.

The compositions, particularly when used as laundry washing or dishwashing compositions, may also comprise enzymes, such
25 as protease, lipase, amylase, cellulase and peroxidase enzymes. Such enzymes are commercially available and sold, for example, under the registered trade marks Esperase, Alcalase, Savinase, Termamyl, Lipolase and Celluzyme by Novo Industries A/S and Maxatasc by International
30 Biosynthetic, Inc. Desirably the enzymes are present in

the composition in an amount of from 0.5 to 3 wt%, especially 1 to 2 wt%.

The compositions may, if desired, comprise a thickening
5 agent or gelling agent. Suitable thickeners are polyacrylate polymers such as those sold under the trade mark CARBOPOL, or the trade mark ACUSOL by Rohm and Haas Company. Other suitable thickeners are xanthan gums. The thickener, if present, is generally present in an amount of
10 from 0.2 to 4 wt%, especially 0.5 to 2 wt%.

The compositions can also optionally comprise one or more additional ingredients. These include conventional detergent composition components such as further
15 surfactants, bleaches, bleach enhancing agents, builders, suds boosters or suds suppressors, anti-tarnish and anti-corrosion agents, organic solvents, co-solvents, phase stabilisers, emulsifying agents, preservatives, soil suspending agents, soil release agents, germicides,
20 phosphates such as sodium tripolyphosphate or potassium tripolyphosphate, pH adjusting agents or buffers, non-builder alkalinity sources, chelating agents, clays such as smectite clays, enzyme stabilizers, anti-limescale agents, colourants, dyes, hydrotropes, dye transfer inhibiting
25 agents, brighteners and perfumes. If used, such optional ingredients will generally constitute no more than 10 wt%, for example from 1 to 6 wt%, of the total weight of the compositions.

30 The builders counteract the effects of calcium, or other ion, water hardness encountered during laundering or

bleaching use of the compositions herein. Examples of such materials are citrate, succinate, malonate, carboxymethyl succinate, carboxylate, polycarboxylate and polyacetyl carboxylate salts, for example with alkali metal or alkaline
5 earth metal cations, or the corresponding free acids. Specific examples are sodium, potassium and lithium salts of oxydisuccinic acid, mellitic acid, benzene polycarboxylic acids, C₁₀-C₂₂ fatty acids and citric acid. Other examples are organic phosphonate type sequestering agents such as
10 those sold by Monsanto under the trade mark Dequest and alkylhydroxy phosphonates. Citrate salts and C₁₂-C₁₈ fatty acid soaps are preferred.

Other suitable builders are polymers and copolymers known to
15 have builder properties. For example, such materials include appropriate polyacrylic acid, polymaleic acid, and polyacrylic/polymaleic and copolymers and their salts, such as those sold by BASF under the trade mark Sokalan.

20 The builders generally constitute from 0 to 3 wt%, more preferably from 0.1 to 1 wt%, by weight of the compositions.

Compositions which comprise an enzyme may optionally contain materials which maintain the stability of the enzyme. Such
25 enzyme stabilizers include, for example, polyols such as propylene glycol, boric acid and borax. Combinations of these enzyme stabilizers may also be employed. If utilized, the enzyme stabilizers generally constitute from 0.1 to 1 wt% of the compositions.

The compositions may optionally comprise materials which serve as phase stabilizers and/or co-solvents. Example are C₁-C₃ alcohols or diols such as methanol, ethanol, propanol and 1,2-propanediol. C₁-C₃ alkanolamines such as mono-, di-
5 and triethanolamines and monoisopropanolamine can also be used, by themselves or in combination with the alcohols. The phase stabilizers and for co-solvents can, for example, constitute 0.1 to 1 wt%, preferably 0.1 to 0.5 wt%, of the composition.

10

If the composition is in liquid form, it may be anhydrous, or, for example, contain up to 5 wt% water. Aqueous compositions generally contain greater than 8 wt% water based on the weight of the aqueous composition. Desirably
15 the aqueous compositions contain more than 10 wt%, 15 wt%, 20 wt%, 25 wt% or 30 wt% water, but desirably less than 80 wt% water, more desirably less than 70 wt%, 60 wt%, 50 wt% or 40 wt% water. They may, for example, contain from 30 to 55 or 65 wt% water.

20

The compositions may optionally comprise components which adjust or maintain the pH of the compositions at optimum levels. Examples of pH adjusting agents are NaOH and citric acid. The pH may be from, for example, 1 to 13, such as 8
25 to 11 depending on the nature of the composition. For example, a dishwashing composition desirably has a pH of 8 to 11, a laundry composition desirably has a pH of 7 to 9, and a water-softening composition desirably has a pH of 7 to 9.

30

The composition may, for example, comprise a component which releases a gas after the container has been sealed which inflates the container to make it look more attractive to a consumer. This component may, for example, comprise a
5 component or a mixture of two or more components which react in the presence of the contents of the container to release the gas. For example, when water is present in the composition, two components which do not react when in solid form but which will react in the presence of water can be
10 added, such as an acid and a carbonate or bicarbonate. An example of a suitable acid is citric acid. Examples of suitable carbonates and bicarbonates are sodium and potassium carbonate and sodium and potassium bicarbonate. If desired, one or more of the components may be
15 encapsulated by a substance which delays the release of the gas.

A further possibility is a component which is a gas at room temperature (20°C) but which, at the time which it is added,
20 is in the form of a solid or liquid because it has been cooled to lessen its melting or boiling point. For example, solid carbon dioxide (dry ice) may be added. As the component heats up to room temperature, which may occur naturally or be aided with heating, it will boil or sublime
25 into a gas. Another possibility is to add a compound which is thermally unstable; for example sodium bicarbonate will release carbon dioxide when it is heated to about 60°C.

The component which releases a gas may also, for example, be
30 a component which gradually releases a gas such as a bleach, in particular an oxygen bleach or a chlorine bleach. Such a

bleach will gradually release a gas such as oxygen or chlorine when it contacts water. The water may itself be contained in the composition, be contained in another compartment and diffuse through the dividing wall into the
5 compartment holding the bleach, or may diffuse into the composition from outside the container.

The gas which is release should desirably be non-toxic or produced in small quantities. It is most convenient,
10 however, to produce carbon dioxide gas since this will not cause any environmental concerns.

The composition may also, for example, be an agricultural composition such as a plant protection agent, for instance a
15 pesticide such as insecticide, acaricide or nematocide, plant growth regulator or a plant nutrient. Such compositions are generally packaged in amounts of from 0.1g to 7 kg, preferably 1 to 7 kg, when in solid form. When in liquid or gelled form, such compositions are generally
20 packaged in amounts of from 0.1 and to 10 litres, preferably 0.1 to 6 litres, especially from 0.5 to 1.5 litres.

The present invention will now be further explained in the following Examples.

25

Example 1

A dishwashing composition was prepared by mixing together the following components in the weight proportions
30 indicated:

	Potassium tripolyphosphate powder	12%
	Sodium tripolyphosphate powder	30%
	Isothiazolinone	0.1%
	Polyacrylate thickener (Carbopol)	1%
5	Nonionic surfactant	0.5%
	Sodium citrate	10%
	Dehardened water	46.4%

A Multivac thermoforming machine operating at 6 cycles/min
10 and at ambient conditions of 25°C and 35% RH ($\pm 5\%$ RH) was
used to thermoform an anhydrous PVOH film. The PVOH film
was prepared by a blown process from granules provided by
PVAXX ref C120 having a degree of hydrolysis of 88% and a
thickness of 110 μm . When formed the PVOH had a negligible
15 water content. The PVOH film was wrapped in a sealed
polyethylene container which remained sealed until
immediately prior to use. The PVOH film was thermoformed
into a rectangular mould of 39mm length, 29mm width and 16mm
depth, with the bottom edges being rounded to a radius of
20 10mm, at 115-118°C. The thus formed pocket was filled with
17ml of the dishwashing composition, and an identical film
was placed on top and heat sealed at 144-148°C. The thus
produced containers were separated from each other by
cutting the flanges. Each container was rounded and had a
25 full appearance. After a few hours they attained an even
more attractive, rounded appearance.

Example 2

30 The following formulations were prepared by mixing together
the indicated components in the weight proportions

indicated. In all instances the compositions were filled into containers following the procedure described in Example 1, and containers having an attractive, rounded appearance were obtained.

5

A laundry detergent composition:

	Sodium carbonate	20%
	Nonylphenol ethoxylate	10%
10	Accusol 820 obtainable from	
	Rohm and Haas Company	3.3%
	Sodium citrate	5%
	Dehardened water	61.7%

15 An automatic dishwasher detergent:

	Sodium citrate	8%
	Van Gel ES thickener obtainable	
	from R.T.Vanderbilt Company	4%
20	Tetrapotassium pyrophosphate	10%
	Sodium tripolyphosphate	30%
	Anhydrous sodium metasilicate	2%
	Sodium xylene sulfonate	2.25%
	Deceth-4-phosphate	0.75%
25	Dehardened water	43%

A slurry-type heavy duty laundry liquid:

	Neodol 25-7 C ₁₂₋₁₅ linear alcohol	18%
30	Biosoft D-62 sodium	
	alkylbenzenesulfonate	5.5%

	Sodium carbonate	2%
	Anhydrous sodium metasilicate	5%
	Tetrasodium pyrophosphate	20%
	Sodium citrate	7.5%
5	Carbopol ETDZ691 polymer	
	obtainable from Goodrich	0.5%
	Dehardened water	41.5%

A slurry-type laundry detergent:

10		
	Sodium carbonate	40%
	Sodium citrate	4.8%
	Accusol 820 obtainable from	
	Rohm and Haas	2%
15	Accusol 810 obtainable from	
	Rohm and Haas	4%
	Sodium tripolyphosphate	10%
	Accusol 445 obtainable from	
	Rohm and Haas	2%
20	Nonylphenol ethoxylate	10%
	Dehardened water	27.2%

A dishwashing composition:

25	Accusol 810	11%
	Accusol 445N	4%
	Sodium tripolyphosphate	20%
	Tetrapotassium pyrophosphate	10%
	Potassium silicate	29%
30	Triton CF-32 alkylamine	
	ethoxylate	3%

Potassium citrate	5%
Dehardened water	18%

CLAIMS

1. A process for preparing a water-soluble container which comprises:
 - 5 a) thermoforming a first poly(vinyl alcohol) film having a water content of less than 5 wt% to produce a pocket;
 - b) filling the pocket with a composition;
 - c) placing a second film on top of the filled pocket;
 - 10 and
 - d) sealing the first film and second film together.
2. A process according to claim 1 wherein the composition in
15 step (b) is an aqueous liquid.
3. A process according to claim 2 wherein the aqueous liquid contains at least 8 wt% water based on the total weight of aqueous liquid.
20
4. A process according to any one of the preceding claims wherein the composition is a fabric care, surface care or dishwashing composition.
- 25 5. A process according to any one of the preceding wherein the container comprises a dishwashing, water-softening, laundry or detergent composition or a rinse aid.
6. A process according to claim 5 wherein the container is
30 suitable for use in a domestic washing machine.

7. A process according to any one of claims 1 to 4 wherein the container comprises a disinfectant, antibacterial or antiseptic composition.
- 5 8. A process according to any one of claims 1 to 4 wherein the container comprises a refill composition for a trigger-type spray.
9. A process according to any one of claims 1 to 3 wherein
10 the container comprises an agricultural composition.
- 10.A process according to any one of the preceding claims wherein the second film is a poly(vinyl alcohol) film.
- 15 11.A process according to claim 10 wherein the second poly(vinyl alcohol) film has a water content of less than 5 wt%.
- 12.A process according to claim 10 wherein the second
20 poly(vinyl alcohol) film has a water content of at least 6 wt%.
- 13.A process according to any one of the preceding claims wherein the first poly(vinyl alcohol) film has a water
25 content of less than 2 wt%.
- 14.A process according to claim 13 wherein the first poly(vinyl alcohol) film has a water content of 0.5 to 1 wt%.

15. Use of a thermoformed poly(vinyl alcohol) film containing less than 5 wt% water to package a composition.
16. Use of a poly(vinyl alcohol) film containing less than 5
5 wt% water and comprising 5 to 35 wt% plasticiser, based on the total weight of the film, to package a composition.
17. Use according to claim 15 or 16 wherein the poly(vinyl
10 alcohol) film contains less than 2 wt% water.

INTERNATIONAL SEARCH REPORT

International Application No

101/GB 01/03790

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 B65B9/04 B65B11/50 B65D65/46

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 B65B B65D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	EP 0 608 910 A (RHONE POULENC AGRICULTURE) 3 August 1994 (1994-08-03) column 2, line 48 -column 6, line 21 ----	1-6, 8-10, 13-15,17
Y	EP 0 937 576 A (WOLFF WALSRÖDE AG) 25 August 1999 (1999-08-25) page 11, line 33 -page 13, line 2 ----	1-6, 8-10, 13-15,17 16
A	WO 94 14941 A (BEROL NOBEL AB ;BERTILSSON BO (SE); CASSEL EVA (SE)) 7 July 1994 (1994-07-07) page 11, line 1 -page 12, line 23 ----	3-5
Y	US 4 973 416 A (KENNEDY SHAUN P) 27 November 1990 (1990-11-27) column 1, line 6 -column 8, line 27 ----- -/-	6

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- * & * document member of the same patent family

Date of the actual completion of the international search

22 November 2001

Date of mailing of the international search report

03/12/2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Jagusiak, A

INTERNATIONAL SEARCH REPORT

Int'l Application No
PCT/GB 01/03790

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 224 601 A (EDWARDS DAVID B ET AL) 6 July 1993 (1993-07-06) ---	
A	EP 0 524 721 A (RHONE POULENC AGROCHIMIE) 27 January 1993 (1993-01-27) ---	
A	US 5 234 615 A (GLADFELTER ELIZABETH J ET AL) 10 August 1993 (1993-08-10) ---	
A	US 4 621 483 A (MAGID DAVID J) 11 November 1986 (1986-11-11) -----	

INTERNATIONAL SEARCH REPORT

Information on patent family members

In: International Application No

PCT/GB 01/03790

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0608910 A	03-08-1994	EP 0608910 A1	03-08-1994
		GR 3024643 T3	31-12-1997
		AP 348 A	28-07-1994
		AT 154564 T	15-07-1997
		AT 154565 T	15-07-1997
		AU 663492 B2	12-10-1995
		AU 1533492 A	02-11-1992
		BR 9205858 A	28-06-1994
		CA 2107341 A1	06-10-1992
		CN 1065436 A ,B	21-10-1992
		CZ 9302063 A3	16-03-1994
		DE 69220483 D1	24-07-1997
		DE 69220483 T2	15-01-1998
		DE 69220501 D1	24-07-1997
		DE 69220501 T2	05-02-1998
		DK 577693 T3	05-01-1998
		DK 608910 T3	29-12-1997
		EP 0577693 A1	12-01-1994
		ES 2104906 T3	16-10-1997
		ES 2106388 T3	01-11-1997
		FI 934354 A	26-11-1993
		WO 9217382 A1	15-10-1992
		GR 3024463 T3	28-11-1997
		HU 65226 A2	02-05-1994
		IE 921094 A1	07-10-1992
		IL 101490 A	15-03-1995
		JP 6506173 T	14-07-1994
		MX 9201538 A1	01-10-1992
		NZ 242248 A	27-01-1995
		PL 171812 B1	30-06-1997
		PT 100349 A	29-04-1994
		RU 2099260 C1	20-12-1997
		SK 107493 A3	08-06-1994
		TR 27730 A	28-06-1995
		ZA 9202467 A	31-03-1993
EP 0937576 A	25-08-1999	DE 19806468 A1	26-08-1999
		EP 0937576 A2	25-08-1999
		US 6274246 B1	14-08-2001
WO 9414941 A	07-07-1994	SE 9203818 A	19-06-1994
		WO 9414941 A1	07-07-1994
US 4973416 A	27-11-1990	JP 2155999 A	15-06-1990
US 5224601 A	06-07-1993	US 5080226 A	14-01-1992
		AP 245 A	04-03-1993
		AP 325 A	09-03-1994
		AP 280 A	03-08-1993
		AP 358 A	03-09-1994
		AP 357 A	03-09-1994
		AP 356 A	03-09-1994
		AT 150253 T	15-04-1997
		AT 184746 T	15-10-1999
		AT 184748 T	15-10-1999
		AT 184747 T	15-10-1999
		AT 184749 T	15-10-1999
		AU 7611491 A	07-11-1991

INTERNATIONAL SEARCH REPORT

Information on patent family members

In International Application No

FCI, GB 01/03790

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5224601	A		AU 8039591 A	23-01-1992
			AU 8039691 A	23-01-1992
			AU 8039791 A	23-01-1992
			AU 8039891 A	23-01-1992
			AU 8039991 A	23-01-1992
			AU 647154 B2	17-03-1994
			AU 8097791 A	18-02-1992
			AU 647155 B2	17-03-1994
			AU 8097891 A	18-02-1992
			AU 651981 B2	11-08-1994
			AU 8105291 A	18-02-1992
			AU 647165 B2	17-03-1994
			AU 8200091 A	18-02-1992
			AU 656325 B2	02-02-1995
			AU 8220391 A	18-02-1992
			BE 1003800 A5	16-06-1992
			BR 9101835 A	17-12-1991
			BR 9105833 A	29-09-1992
			BR 9105834 A	29-09-1992
			BR 9105835 A	29-09-1992
			BR 9105836 A	29-09-1992
			BR 9105837 A	29-09-1992
			CA 2041313 A1	03-11-1991
			CA 2065159 A1	19-01-1992
			CA 2066243 A1	19-01-1992
			CA 2066405 C	17-06-1997
			CA 2066419 C	17-06-1997
			CA 2066424 C	20-09-1994
			CH 684468 A5	30-09-1994
			CN 1058317 A	05-02-1992
			CN 1058318 A	05-02-1992
			CN 1058319 A	05-02-1992
			CN 1058191 A ,B	29-01-1992
			CN 1058320 A	05-02-1992
			CS 9101249 A2	17-12-1991
			CS 9102215 A3	19-02-1992
			CS 9102216 A3	19-02-1992
EP 0524721	A	27-01-1993	US 5139152 A	18-08-1992
			AP 407 A	25-09-1995
			AP 445 A	12-01-1996
			AP 442 A	12-12-1995
			AT 183614 T	15-09-1999
			AU 664996 B2	14-12-1995
			AU 1802392 A	24-12-1992
			AU 664997 B2	14-12-1995
			AU 1809192 A	17-12-1992
			AU 664998 B2	14-12-1995
			AU 1809292 A	17-12-1992
			BR 9202306 A	05-01-1993
			BR 9202307 A	05-01-1993
			BR 9202308 A	05-01-1993
			CA 2071075 A1	12-12-1992
			CA 2071076 A1	12-12-1992
			CA 2071077 A1	12-12-1992
			CN 1067859 A	13-01-1993
			CN 1067630 A	06-01-1993
			CN 1067629 A	06-01-1993

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 01/03790

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0524721 A		CS 9201758 A3	16-12-1992
		CS 9201759 A3	16-12-1992
		CS 9201760 A3	16-12-1992
		DE 69229849 D1	30-09-1999
		EP 0524721 A1	27-01-1993
		EP 0518629 A1	16-12-1992
		EP 0522713 A1	13-01-1993
		FI 922681 A	12-12-1992
		FI 922682 A	12-12-1992
		FI 922683 A	12-12-1992
		IE 921879 A1	16-12-1992
		IE 921880 A1	16-12-1992
		IE 921881 A1	16-12-1992
		IL 102128 A	16-10-1996
		JP 5155705 A	22-06-1993
		JP 5155704 A	22-06-1993
		JP 5155708 A	22-06-1993
		MX 9202757 A1	31-05-1994
		MX 9202759 A1	31-05-1994
		MX 9202762 A1	31-05-1994
		NZ 243094 A	22-12-1994
		NZ 243095 A	27-09-1994
		NZ 243096 A	27-09-1994
		US 5280835 A	25-01-1994
		US 5624034 A	29-04-1997
		ZA 9204232 A	31-03-1993
		ZA 9204233 A	31-03-1993
		ZA 9204234 A	31-03-1993
		AP 346 A	28-07-1994
US 5234615 A	10-08-1993	US 5078301 A	07-01-1992
		AU 648865 B2	05-05-1994
		AU 1066192 A	26-03-1992
		AU 2297988 A	06-04-1989
		BR 8805071 A	09-05-1989
		CA 1309062 A1	20-10-1992
		DE 3853612 D1	24-05-1995
		DE 3853612 T2	18-01-1996
		EP 0314890 A2	10-05-1989
		JP 1240461 A	26-09-1989
		JP 2688074 B2	08-12-1997
		MX 172057 B	01-12-1993
		NZ 225512 A	27-11-1990
		US 5198198 A	30-03-1993
US 4621483 A	11-11-1986	US 4478044 A	23-10-1984
		AU 543492 B2	18-04-1985
		AU 8533882 A	10-02-1983
		BR 8204392 A	19-07-1983
		CA 1188273 A1	04-06-1985
		DE 3272880 D1	02-10-1986
		DE 3279341 D1	16-02-1989
		DE 3280391 D1	05-03-1992
		EP 0071733 A2	16-02-1983
		EP 0171556 A1	19-02-1986
		EP 0296388 A1	28-12-1988
		ES 514722 D0	16-10-1983
		ES 8400331 A1	16-01-1984

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 01/03790

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4621483	A	ES 521156 D0	01-04-1984
		ES 8403820 A1	01-07-1984
		ES 521157 D0	01-10-1984
		ES 8500172 A1	01-01-1985
		ES 532495 D0	01-04-1985
		ES 8504058 A1	01-07-1985
		IE 54616 B1	20-12-1989
		IE 54617 B1	20-12-1989
		IL 66180 A	16-09-1987
		IL 74618 A	16-09-1987
		JP 7025387 B	22-03-1995
		JP 58112979 A	05-07-1983
		KR 8901506 B1	06-05-1989
		MX 161752 A	20-12-1990